



VRLA Battery SPA 12-28

Specifications





Nominal Voltage 12 V

Rated Capacity (25 °C)	20hr Rate (1,80V/cell)	10hr Rate (1,80V/cell)	5hr Rate (1,70V/cell)	1hr Rate (1,60V/cell)	
	27,4 Ah	25,6 Ah	24,0 Ah	18,2 Ah	
Dimensions (mm)	Length	Width	Height	Overall Height	Weight
& Weight (kg)	165mm	125mm	175mm	182mm	9,30kg

Number / Type of Terminals 2 / F3

Technical Characteristics

Design Life at 20°C	5 years
Eurobat Classification	Standard Commercial
Internal Resistance (Fully charged - 25°C)	8 mΩ
Short-circuit current	1400 A
Max Charging Current	11,2 A
Min safe end Discharge Voltage	1,60 V/cell
Self discharge per month at 20°C	3%
Recommended Charging Voltage at 20°C	Stand-by use (V/cell): 2,25 to 2,30 Cycle use (V/cell): 2,40 to 2,50
Container Material	ABS-UL94 HB
Electrolyte Type	Sulfuric Acid
Type of plates / Alloy	Flat plates / Lead-Calcium-Tin alloy
Type of Separator	Absorbant Glass Mat
Valve Type / Operational Pressure	Rubber / 1-3 psi (70-200 mbar)
Operating Temperature Range	-20 to +50°C
Storage time at 20°C	9 months



Terminal F3

SYSTEMS SUNLIGHT S.A.

Headquarters

2 Ermou & Nikis Str., Syntagma Sq.
105 63 Athens, Attica, Greece
T +30 210 6245400 F +30 210 6245409
European Manufacturing Plant
672 00 Neo Olvio, Xanthi, Greece
T +30 25410 48100 F +30 25410 95446

Global Service Department

366 Tatoiou Str.
136 73 Acharnes, Attica, Greece
T +30 210 6245600 F +30 210 6245619

 **SUNLIGHT**
Reliable Battery Solutions

www.systems-sunlight.com